

MANUFACTURE OF BATTERY AND BATTERY SEPARATOR

Publication number: JP7094162

Publication date: 1995-04-07

Inventor: TAKAHASHI NORIMASA; OO FUMIO

Applicant: MATSUSHITA ELECTRIC IND CO LTD

Classification:

- international: **H01M2/16; H01M6/12; H01M2/16; H01M6/04; (IPC1-7):**
H01M2/16; H01M6/12

- european:

Application number: JP19930241093 19930928


Priority number(s): JP19930241093 19930928

Report a data error here

Abstract of JP7094162

PURPOSE: To provide a separator having high closing voltage without any increase in the specific resistance thereof by filling space between each separator with a deaerated water soluble resin solution, and making the separators adhere to each other.

CONSTITUTION: A button type alkaline battery (SR626) is formed out of a sealing plate as a negative terminal in common, a negative electrode active material 2, a separator 3 made of a polyethylene graft film and the first cellophane, the second cellophane and nonwoven fabric, a positive electrode material 4, a positive electrode case 5 and an insulation packing 6. For the preparation of the separator 3, four layers of the tape type polyethylene graft film, the first cellophane, the second cellophane and the nonwoven fabric are coiled like a roll, while a polyvinyl alcohol solution deaerated in advance is being applied between separator materials, and, then, dried in vacuum at a temperature of 30 deg.C for two minutes, thereby providing the separator 3.



Data supplied from the esp@cenet database - Worldwide